

TPS Door operated switch

suitable for ALLIO and ALU-LINE series



IP20

Made in
Germany

CE

UK
CA

RoHS
compliant

REACH
COMPLIANCE

Specifications

IP rating (EN 60529)	IP20
Material	Polyamide
Flame class	
Operating temperature	-20 C° to 50 C°
Mounting options	Screw type mounting

Advantages & benefits

- Easy adjustment
- Flat, space-saving design
- Reliable, direct switching
- Integrated cable routing
- Assembly on surfaces and profiles of various manufacturers
- Snap-on assembly aid on profiles
- Also suitable for exterior doors
- With connecting cable and straight or angled connector
- Adapters for enclosures from Rittal, Hofmann, Eldon and Triton as well as for assembly on surfaces are included in the scope of delivery

Product types & sizes

Door operated switch, 600 mm



Part No.	81132	Length	600 mm
EAN	4251269333071	connecting cable	
Package quantity	1	Connector type	C8 connector
UL Certificate	-	Rated current	2,5 A
Length	85,2 mm	Colour	black
Height	24 mm		
Width	63,2 mm		

Door operated switch, 600 mm



Part No.	81334	Length	600 mm
EAN	4251269333002	connecting cable	
Package quantity	1	Connector type	C8 connector, angled
UL Certificate	-	Rated current	2,5 A
Length	85,2 mm	Colour	black
Height	24 mm		
Width	63,2 mm		

Door operated switch, 1500 mm



Part No.	81133	Length	1.500 mm
EAN	4251269333088	connecting cable	
Package quantity	1	Connector type	C8 connector
UL Certificate	-	Rated current	2,5 A
Length	85,2 mm	Colour	black
Height	24 mm		
Width	63,2 mm		

Door operated switch, 1500 mm



Part No.	81333	Length	1.500 mm
EAN	4251269332999	connecting cable	
Package quantity	1	Connector type	C8 connector, angled
UL Certificate	-	Rated current	2,5 A
Length	85,2 mm	Colour	black
Height	24 mm		
Width	63,2 mm		

